

502,236

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
31 July 2003 (31.07.2003)

PCT

(10) International Publication Number  
**WO 03/062176 A1**

(51) International Patent Classification<sup>7</sup>: C07C 7/12,  
C10G 25/02, B01J 41/04, 41/14

(21) International Application Number: PCT/GB03/00184

(22) International Filing Date: 17 January 2003 (17.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0201457.9 23 January 2002 (23.01.2002) GB  
0201461.1 23 January 2002 (23.01.2002) GB

(71) Applicant (for all designated States except US): **JOHN-  
SON MATTHEY PLC** [GB/GB]; 2-4 Cockspur Street,  
Trafalgar Square, London SW1Y 5BQ (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **CARNELL, Peter,**  
**John, Herbert** [GB/GB]; 50 Hartburn Village, Stockton  
on Tees, Cleveland TS18 5DP (GB). **YOUNG, Nicola**  
[GB/GB]; 26 Hamilton Drive, Darlington, County Durham  
DL1 3TS (GB). **WOOD, Peter** [GB/GB]; 98 Grange  
Avenue, Stockton on Tees, Cleveland TS18 4PR (GB).

(74) Agents: **GIBSON, Sara, Hillary, Margaret** et al.; Syntex  
Intellectual Property Department, P.O. Box 1, Belasis Av-  
enue, Billingham, Cleveland TS23 1LB (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN,  
YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,  
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report
- before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments

✓ For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: SULPHIDED ION EXCHANGE RESINS

(57) Abstract: Sulphided ion exchange resins containing primary or secondary amino groups. They may be obtained by passing a non-aqueous liquid, e.g. a hydrocarbon, feedstock containing elemental sulphur or organic, or inorganic, di- or poly-sulphides through a bed of an ion exchange resin containing primary or secondary amino groups, and so unsulphided ion exchange resins containing primary or secondary amine groups may be used to remove such elemental sulphur or sulphur compounds from liquid, e.g. hydrocarbon, feedstocks. The sulphided ion exchange resins may be used to remove elemental mercury or organic mercury compounds from liquid, e.g. hydrocarbon, streams.

WO 03/062176 A1

Sulphided ion exchange resins.

This invention relates to sulphided ion exchange resins and their production and use.

Accordingly the invention provides a sulphided ion exchange resin containing  
5 primary or secondary amino groups.

Elemental sulphur or organic, or inorganic, di-or poly-sulphides may be present as a contaminant in liquids especially hydrocarbons. One source of such contamination is as a result of the transport of hydrocarbons via pipelines. In some cases batches of different hydrocarbons are pumped along a pipeline in sequence and  
10 as a result "clean" hydrocarbons such as gasoline may be contaminated by materials such as hydrogen sulphide from the previous use of the pipeline for a "dirty" hydrocarbon such as kerosene. Pipeline scale and/or ingress of small amounts of air can cause the oxidation of contaminants such as hydrogen sulphide to elemental sulphur. Sublimation of elemental sulphur may also result in contamination of gaseous  
15 hydrocarbons.

Removal of such elemental sulphur and sulphur compounds is desirable. We have found that ion exchange resins containing primary or secondary amino groups can absorb significant amounts of elemental sulphur.

Accordingly the present invention also provides a method of making sulphided  
20 ion exchange resins containing primary or secondary amino groups comprising passing a non-aqueous liquid feedstock containing elemental sulphur or organic, or inorganic, di-or poly-sulphides through a bed of an ion exchange resin containing primary or secondary amino groups.

The process may thus be employed for the removal of such sulphur or sulphur  
25 compounds present as contaminants in liquid, e.g. hydrocarbon, feedstocks.

The absorption may be effected at temperatures in the range  $-10^{\circ}\text{C}$  to  $+100^{\circ}\text{C}$  and under sufficient pressure that the feedstock is in the liquid, by which term we include gases in the "dense phase", state at the desired absorption temperature. By the term "dense phase" we mean that the fluid is at a pressure that is above the upper  
30 dew point curve and at a temperature above the critical temperature (but generally below the temperature of the maxcondentherm point - which is the maximum temperature of the dew point and bubble point curves).

Amine-containing ion exchange resins as supplied often contain a significant amount of water. We have found that such water can retard the absorption of

elemental sulphur. Accordingly it is preferred that the ion exchange resin is dried, e.g. by extraction with a suitable solvent such as methanol, before use. The ion exchange resin, of which Amberlyst A.21 is a typical example, is preferably employed in the form of a fixed bed of shaped units, e.g. spherical granules, preferably having maximum and minimum dimensions in the range 0.5 to 10 mm.

As a result of the aforesaid process, the ion exchange resin becomes sulphided. In addition to absorbing the elemental sulphur, the ion exchange resin may catalyse the decomposition of elemental sulphur species such as the cyclic  $S_8$  species, forming polysulphides and hydrogen sulphide. Consequently it may be desirable to pass the feedstock through a bed of a suitable hydrogen sulphide absorbent after passage through the bed of the ion exchange resin. Suitable hydrogen sulphide absorbents include zinc and copper compounds such as oxides, hydroxides and basic carbonates. A particularly suitable absorbent that is effective at the temperatures mentioned above comprises agglomerates of co-precipitated copper, zinc and aluminium compounds and may contain a suitable binder, e.g. a calcium aluminate cement.

Liquid feedstocks that may be treated include any non-aqueous liquids that are liquid under the operating conditions. Preferred hydrocarbons include natural gas liquids and gasoline.

If desired, the ion exchange resin can be regenerated by periodic treatment with a suitable acid such as hydrochloric acid. However under favourable conditions, the ion exchange resin may have the capacity to absorb a sufficient amount of sulphur that it is economic to replace the resin when laden with the absorbed sulphur rather than to provide for regeneration. Alternatively the sulphided ion exchange resin may be used to adsorb elemental mercury and/or organic mercury compounds as described below.

In addition to, or instead of, sulphur compounds, elemental mercury and/or organic mercury compounds may be present as a contaminant in non-aqueous fluids, e.g. hydrocarbon, streams, e.g. gas or oil as extracted from the earth. The presence of mercury or organic mercury compounds is undesirable since elemental mercury can cause severe corrosion problems while organic mercury compounds tend to be toxic and/or readily decomposed to elemental mercury. Removal of such elemental mercury and organic mercury compounds is desirable. We have found that sulphided ion exchange resins containing primary or secondary amino groups, for example as obtained in the aforesaid process, can absorb significant amounts of mercury.

Accordingly the present invention provides a method for the removal of mercury and organic mercury compounds from a non-aqueous liquid, e.g. hydrocarbon, feedstock comprising passing the feedstock through a bed of a sulphided ion exchange resin containing primary or secondary amino groups.

5        As for the original sulphiding process, the absorption may be effected at temperatures in the range  $-10^{\circ}\text{C}$  to  $+100^{\circ}\text{C}$  and under sufficient pressure that the feedstock is in the liquid or "dense phase", state at the desired absorption temperature.

10       In addition to absorbing the elemental mercury, the sulphided ion exchange resin may remove organic mercury compounds by catalysing their decomposition with the absorption of the mercury thus formed or by other means.

15       Where the liquid feedstock stream also contains sulphur, the ion exchange resin may be sulphided in situ. However, in order to ensure that the mercury is absorbed, it is preferred that at least the inlet portion of the bed of ion exchange resin is sulphided before a mercury containing stream is passed through the bed.

Hydrocarbons that may be treated include any that are liquid under the operating conditions. Preferred hydrocarbons include natural gas liquids and gasoline.

The invention is illustrated by the following examples.

#### Example 1

20       A stirred vessel was charged with 200 ml of toluene in which about 10 mg of sulphur had been dissolved at room temperature. 5 g of an ion exchange resin, Amberlyst A.21 which contains methylamino groups, in the form of spherical granules of diameter about 1.5 mm was added to the vessel and stirring continued. Samples of the solution were taken for analysis at intervals. As no significant reduction in the  
25       sulphur content occurred after 165 minutes, a further 5 g of the ion exchange resin was added and stirring, and intermittent sampling, continued for a further 3 hours. Stirring was then stopped and the vessel left to stand for 7 days. The sulphur content of the solution is shown in the Table 1.

Table 1

Time	Total sulphur content (mg/l)
0 min	45.5
10 min	46.1
30 min	46.1
165 min	44.1
210 min	34.3
300 min	18.2
345 min	8.3
7 days	0

It is seen that the sulphur was only absorbed slowly.

Example 2

The procedure of example 1 was repeated without the addition of the second 5 g  
5 of ion exchange resin and the vessel was left to stand for 3 days. The results are  
shown in Table 2.

Table 2

Time	Total sulphur content (mg/l)
0 min	44.1
30 min	43.2
60 min	44.0
180 min	40.7
240 min	35.8
315 min	23.0
360 min	14.5
3 days	3.5

Example 3

Analysis of the Amberlyst A 21 ion exchange resin as used in Examples 1 and 2 revealed that its initial water content was about 50% by weight. In order to reduce the water content, 10 g of the Amberlyst A21 resin was extracted in a separating funnel with two 50 ml aliquots of methanol. The methanol was then drained off and the resin dried in a stream of nitrogen. The procedure of Example 2 was then repeated using the extracted resin and a solution of 13 mg of sulphur in 200 ml of toluene. The results are shown in Table 3.

Table 3

Time (min)	Total sulphur content (mg/l)
0	44.5
30	37.0
90	0.04
220	0

It is seen that the sulphur was rapidly absorbed.

Example 4

To assess the capacity of the Amberlyst A 21 ion exchange resin for sulphur, 5 g of the resin was added to a solution of 2527 mg of sulphur in 200 ml of toluene. Samples of the resin were removed at intervals, air dried and then analysed for total sulphur. The results are shown in Table 4.

Table 4

Time (hours)	sulphur content (mg/cm <sup>3</sup> )
5.5	14
7	19
24	41
51	51

Claims

1. A sulphided ion exchange resin containing primary or secondary amino groups.
2. A method according to claim 1 wherein the ion exchange resin is in the form of a fixed bed of shaped units having maximum and minimum dimensions in the range 0.5 to 10 mm.
3. A method for the production of a sulphided ion exchange resin according to claim 1 or claim 2 comprising passing a non-aqueous liquid feedstock containing elemental sulphur or organic, or inorganic, di- or poly-sulphides through a bed of an ion exchange resin containing primary or secondary amino groups.
4. A method for the removal of elemental sulphur from a non-aqueous liquid feedstock comprising passing the feedstock through a bed of an ion exchange resin containing primary or secondary amino groups.
5. A method according to claim 4 wherein the feedstock is passed through a bed of a hydrogen sulphide absorbent after passage through the bed of the ion exchange resin.
6. A method according to any one of claims 3 to 5 wherein water is removed from the ion exchange resin before use.
7. A method according to any one of claims 3 to 6 wherein the feedstock is contacted with the ion exchange resin bed at temperatures in the range -10°C to +100°C under sufficient pressure that the feedstock is in the liquid state.
8. A method according to any one of claims 3 to 7 wherein the ion exchange resin is periodically regenerated by treatment with an acid.

9. A method according to any one of claims 3 to 8 where the liquid is a hydrocarbon.
10. A method for the removal of mercury and organic mercury compounds from a non-aqueous liquid feedstock comprising passing the feedstock through a bed of a sulphided ion exchange resin containing primary or secondary amino groups according to claim 1 or claim 2 or made by a process according to any one of claims 3 to 9.
11. A method according to claim 10 wherein the feedstock is contacted with the ion exchange resin bed at temperatures in the range  $-10^{\circ}\text{C}$  to  $+100^{\circ}\text{C}$  under sufficient pressure that the feedstock is in the liquid state.
12. A method for the removal of elemental sulphur and of mercury and organic mercury compounds from a non-aqueous liquid feedstock comprising passing the feedstock through a bed of an ion exchange resin containing primary or secondary amino groups wherein at least the inlet portion of the bed of ion exchange resin is sulphided before a mercury containing stream is passed through the bed.
13. A method according to any one of claims 10 to 12 wherein the liquid is a hydrocarbon.



## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/JP03/00184

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C07C7/12 C10G25/02 B01J41/04 B01J41/14

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C07C C10G B01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DATABASE WPI Section Ch, Week 199807 Derwent Publications Ltd., London, GB; Class A26, AN 1998-075485 XP002235001 & RU 2 081 130 C (UNIV MENDELEEV CHEM TECHN), 10 June 1997 (1997-06-10) abstract	1
X	DATABASE WPI Section Ch, Week 199303 Derwent Publications Ltd., London, GB; Class H02, AN 1993-021908 XP002235002 & JP 04 348188 A (MITSUBISHI PETROCHEMICAL CO LTD), 3 December 1992 (1992-12-03) abstract	1, 10, 12

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

23 May 2003

Date of mailing of the international search report

10/06/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Hilgenga, K

BEST AVAILABLE COPY

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/ 03/00184

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DD 224 038 A (BITTERFELD CHEMIE) 26 June 1985 (1985-06-26) the whole document ---	1,10
X	US 4 614 592 A (GOOGIN JOHN M ET AL) 30 September 1986 (1986-09-30) claim 1 ---	1
X	US 2 592 523 A (AYERS GEORGE W ET AL) 15 April 1952 (1952-04-15) column 5, line 1 - line 29 ---	1
A	US 5 401 393 A (WHITEHURST DARRELL D ET AL) 28 March 1995 (1995-03-28) claims 1-3 ---	1-3,10, 12,13
A	EP 0 319 615 A (STAMICARBON) 14 June 1989 (1989-06-14) the whole document ---	10,12,13
A	FR 2 512 051 A (RAFFINAGE CIE FRANCAISE) 4 March 1983 (1983-03-04) claims 1,9 ---	4
A	US 6 027 636 A (POIRIER MARC-ANDRE) 22 February 2000 (2000-02-22) claim 1 -----	4,9

BEST AVAILABLE COPY

## INTERNATIONAL SEARCH REPORT

International Patent No.

PCT/JP/00184

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
RU 2081130	C	10-06-1997	RU 2081130 C1	10-06-1997
JP 4348188	A	03-12-1992	JP 2873102 B2	24-03-1999
DD 224038	A	26-06-1985	DD 224038 A1	26-06-1985
US 4614592	A	30-09-1986	NONE	
US 2592523	A	15-04-1952	NONE	
US 5401393	A	28-03-1995	AU 7632494 A WO 9507958 A1	03-04-1995 23-03-1995
EP 319615	A	14-06-1989	EP 0319615 A1 AT 73165 T AU 2656988 A BR 8806500 A CA 1336647 A1 DE 3777190 D1 ES 2032291 T3 FI 885734 A ,B, GR 3004683 T3 JP 2138394 A JP 2569157 B2 KR 9107459 B1 NO 885475 A ,B, PT 89190 A ,B SG 48792 G US 4950408 A	14-06-1989 15-03-1992 15-06-1989 22-08-1989 15-08-1995 09-04-1992 01-02-1993 12-06-1989 28-04-1993 28-05-1990 08-01-1997 26-09-1991 12-06-1989 29-12-1989 12-06-1992 21-08-1990
FR 2512051	A	04-03-1983	FR 2512051 A1	04-03-1983
US 6027636	A	22-02-2000	US 5951851 A	14-09-1999